



JIS B220 -1995, JIS B210-1984

単位:mm

呼び径		SO形、SW形						WN形					重量(kg)				
		内径部詳細						内径	ハブ部分		全長	半径	半径	SO形	WN形	PL形	BL形
									ハブ先	ハブ元							
inch	mm	S1	m	S2	n	α°	ℓ	B	A	X	T	R	r				
3/8	10	-	-	-	-	-	-	-	-	-	-	-	-	0.99	-	1.0	1.0
1/2	15	31	4.0	40	5	-	-	15.8	22.0	40	45	20	6	1.23	1.33	1.2	1.3
3/4	20	37	5.0	44	5	-	-	21.1	27.5	44	45	20	6	1.34	1.47	1.3	1.4
1	25	44	6.0	52	5	-	-	26.8	34.4	52	48	20	6	1.76	1.95	1.7	1.9
1 1/4	32	52	6.0	60	5	°	°	35.1	43.1	62	52	30	6	2.15	2.43	2.2	2.5
1 1/2	40	58	6.0	66	5	-	-	40.7	49.1	70	54	30	6	2.82	3.16	2.9	3.2
2	50	70	6.5	78	5	-	-	52.2	61.0	84	57	30	8	2.89	3.33	3.8	3.3
2 1/2	65	96	9.5	94	5	20°	6	65.3	76.9	104	69	30	8	5.10	5.91	4.8	5.8
3	80	109	9.5	-	-	20°	6	76.4	89.7	118	73	30	8	5.83	7.05	5.6	7.0
3 1/2	90	122	9.5	-	-	20°	6	89.5	102.3	130	74	30	8	7.28	8.54	7.0	9.0
4	100	135	9.5	-	-	20°	6	101.5	115.1	142	76	30	8	8.10	9.72	7.8	10.4
5	125	160	9.5	-	-	20°	6	125.7	140.7	172	86	50	10	12.3	14.4	11.4	15.8
6	150	186	9.5	-	-	20°	6	150.0	166.2	202	95	50	10	17.1	20.6	16.3	22.8
8	200	237	9.5	-	-	20°	6	198.7	217.5	254	102	50	10	22.4	28.7	21.1	33.4
10	250	290	10.0	-	-	20°	6	247.5	268.7	312	118	50	12	37.9	47.3	35.0	56.4
12	300	345	12.0	-	-	30°	6	296.4	320.0	366	127	50	15	49.9	62.8	47.0	79.9
14	350	383	13.0	-	-	30°	6	331.8	357.2	406	134	80	15	61.2	77.0	56.6	99.2
16	400	435	14.0	-	-	30°	7	379.1	408.3	462	149	80	20	85.0	108.0	76.9	138.6